MAX-Clean

MAX-Clean is an emulsified blend of water-soluble surfactants and solvents designed to remove synthetic mud and other hydrocarbon oils from metal surfaces such as casing, risers, work strings, and surface equipment before completion operations. MAX-Clean leaves the metal surfaces water-wet.

MAX-Clean can be incorporated into the displacement spacers to transition nonaqueous drilling fluid to completion fluid, eliminating spacer contamination and waste.

Advantages

- Is effective in all types and densities of completion fluids
- Is environmentally friendly with UK CEFAS Gold HQ value
- Is biodegradable, nontoxic, nonflammable, and noncorrosive
- Removes synthetic mud and other hydrocarbon oils from metal surfaces, leaving a water-wet surface
- Disperses oil-coated solids into small droplets that do not commingle or agglomerate

Applications

MAX-Clean is used as a 5 to 20 percent solution in seawater or other water-based brines.

Usage

Optimal treatment concentration varies depending upon the specific application. Consult the MSDS, safety posters, and/or product label before use, and use personal protective equipment as advised.

Typical Physical Properties

Appearance	Amber liquid
Specific gravity	0.86 to –0.90
Flash point (T.O.C.)	> 141ºF *> 60ºC*
Solubility (in water)	Soluble
Packaging (drums, isotanks, bulk)	55-gal *208-L*

© 2012 Weatherford. All rights reserved. **9401.00**

The information contained herein was accurate and reliable to the best of our knowledge at the time this document was prepared. The material is supplied solely for information purposes, and Weatherford makes no guarantees or warranties, expressed or implied, with respect to its accuracy. Ensuring the completeness and accuracy of such information is the responsibility of the user of this product. Always consult the Material Safety Data Sheet for this product before use. Weatherford products and services are subject to the Company's standard terms and conditions, available on request or at weatherford.com. For more information contact an authorized Weatherford representative. Unless noted otherwise, trademarks and service marks herein are the property of Weatherford and may be registered in the United States and/or other countries. Weatherford products named herein may be protected by one or more U.S. and/or foreign patents. For more information, contact patents@weatherford.com. Specifications are subject to change without notice. Weatherford sells its products and services in accordance with the terms and conditions set forth in the applicable contract between Weatherford and the client.