

RFID Optibarrier™ Ball Valve

Remotely opened, multi-cycle downhole isolation valve installs confidence in your well barrier envelope

Applications

- Isolating the lower completion system for upper completion installation or workovers
- Hydraulically setting production packers
- Deepset barriers
- Fluid loss applications

Features and Benefits

- The RFID Optibarrier ball valve can be operated using industry-standard shifting tools for operational flexibility.
- The ball valve has increased differential opening capacity.
- The ball valve provides unlimited mechanical opening and closing functionality.
- The fullbore inside diameter (ID) of the ball valve maximizes production and enhances access to the formation.
- The bidirectional sealing mechanism provides a robust downhole barrier.
- The ball mechanism rotationally locks to facilitate contingency milling.

Tool Description

The Weatherford Optibarrier ball valve is a tubing-mounted bidirectional ball valve that can be opened and closed remotely using a radio-frequency identification (RFID) enabled control module. It can also be opened mechanically using industry-standard shifting tools or a stinger module assembled into an upper completion or workstring.

Tested beyond the International Organization for Standardization (ISO) 28781-V1 standards and in accordance with the American Petroleum Institute (API) specification 19-V1, the bidirectional sealing mechanism provides a reliable downhole barrier. When open, the fullbore ID maximizes flow area and enables access to the formation. The ball valve can be manufactured in a variety of metallurgies, ranging from basic 4140 to high-nickel premium alloys.



The Weatherford Optibarrier mechanical ball valve has a modular design that is compatible with other Optibarrier products.



RFID Optibarrier™ Ball Valve

Specifications

Size in. (mm)	Max. OD in. (mm)	Min. ID in. (mm)	Maximum Differential Rating Across Ball* psi (MPa)	Absolute Pressure Rating psi (MPa)	Temperature °F (°C)	Connections	Qualification Standard
4.50 in. (114.3 mm)	7.75/8.00 in. (196.9 mm 203.2mm)	3.75 in. (95.3 mm)	10,000 psi (68.9 MPa)	15,000 (103.4)	39-302 (4-150)	4-1/2 in. Premium	API 19V1
5.50 in. (216.0 mm)	8 in. (203.2 mm)	4.63 in. (117.6 mm)	7,500 psi (51.7 MPa)	15,000 (103.4)	39-302 (4-150)	5-1/2 in. Premium	API 19V1

*The maximum differential ratings across the ball are metallurgy dependent.

