

REAL RESULTS

ZoneSelect[™] Fracturing System Isolates, Fractures Long-Reach Horizontal Well, Maximizes Reservoir Access

Objectives

- Install a multi-zone liner system with openhole packers and sleeves.
- Isolate and fracture multiple zones in a 20,111-ft (6130-m) horizontal well. The operator experienced well kickoff at 6,145 ft (1873 m) and the total horizontal section was approximately 13,123 ft (4000 m).
- · Maximize reservoir exposure and inflow capability.


Results

- The operator successfully deployed Weatherford's *ZoneSelect* SingleShot Frac Sliding Sleeves and ARES hydraulic openhole isolation packers to a total depth of 20,111 ft (6130 m).
- Weatherford used 18 *ZoneSelect* sleeves and 22 ARES packers to isolate 21 intervals and stimulate 18 of them in a single wellbore.
- The ARES packers isolated each stage's fracture treatment.
- Weatherford's ZoneSelect SingleShot Frac Sliding Sleeves maximized the operator's flow area through the flow ports while protecting the inner sleeve from erosion.

Value to Client

- Using Weatherford's *ZoneSelect* SingleShot Frac Sliding Sleeves and the ARES packers enabled the operator to create zonal isolation in a horizontal well and conduct multiple fracturing operations.
- Isolating zones in an openhole environment enabled the operator to expose a larger surface area for fracturing, increasing production 25% over an 18-month period.
- The *ZoneSelect* system minimized extraneous time and services required to stimulate the well, saving the operator associated rig costs and reducing the overall environmental impact.

Weatherford Randal Biedermann Sales Manager, Completion Systems randal.biedermann@ca.weatherford.com



Weatherford's ARES openhole packers and *ZoneSelect* technology isolated 21 individual zones in a 20,111-ft (6130-m) lateral well, decreasing overall costs while increasing production rates.

Location Canada

Formation Montney

Well Type Onshore, horizontal

Hole Size 6-1/8 in. (156 mm)

Depth 20,111 ft (6130 m) MD 7,053 ft (2150 m) TVD

Liner Casing 4 1/2-in., 15.1-lb/ft (114.3-mm, 22.47-kg/m) L-80

Equipment

- ZoneSelect SingleShot Frac sliding sleeves
- ARES openhole isolation packers
- UltraPak U Series permanent liner top packer assembly
- Premium latch seal assembly

Weatherford products and services are subject to the Company's standard terms and conditions, available on request or at weatherford com. For more information contact an authorized Weatherford representative. Unless noted otherwise, trademarks and service marks herein are the property of Weatherford and may be registered in the United States and/or other countries. Weatherford products named herein may be protected by one or more U.S. and/or foreign patents. For more information, contact patents²⁰/weatherford.com. Specifications are subject to change without noice. Weatherford statis bis products and services in accordance with the terms and conditions set forth in the applicable contract between Weatherford and the client.