

REAL RESULTS

ZoneSelect[®] Technology Overcomes Washout Conditions, Isolates 5 Zones, Saves Rig Time, Costs

Objectives


 Install a ZoneSelect fracturing completion system in an 8 1/2-in. open hole, and cement in place to eliminate washout issues in the wellbore.

Results

- The client enlisted Weatherford to deploy a 5 1/2-in. *ZoneSelect* SingleShot system with cementation accessories for five zones. The cementing accessories are derived from Weatherford's existing cementation product line, which to-date has achieved a very high standard and success rate in the industry.
- A wiper dart was specially designed to wipe clean the cement from the inside of the SingleShot sleeves and to pass through the ball-seat restrictions.
- The combined system was successfully deployed with no issues, after which a 10,000-psi (68.9-MPa) system was also successfully deployed in the wellbore.

Value to Client

- Using Weatherford's *ZoneSelect* SingleShot system and cementing equipment enabled the operator to create zonal isolation in five zones and meet predetermined pressure limitations.
- The ZoneSelect system minimized extraneous time and services required to stimulate the well, saving the associated rig costs and reducing the overall environmental impact.



In a well experiencing openhole washout issues, packers were unable to be used. To overcome the wellbore conditions, Weatherford cemented *ZoneSelect* technology in place, a first for China, and isolated five individual zones in a 8,908-ft (2715.20-m) well, decreasing overall costs while increasing production rates.

Location China

Well Type Onshore, oil

Formation Sandstone

Hole Size 8-1/2 in.

Depth

8,908 ft (2715.20 m)

Casing

5 1/2-in. 17 lb/ft (25.33 kg/m) (cemented to surface)

Products/Services

- ZoneSelect SingleShot fracturing sleeves
- ZoneSelect toe fracturing sleeve
- Wiper dart
- Landing collar
- Float shoe

Weatherford products and services are subject to the Company's standard terms and conditions, available on request or at weatherford.com. For more information contact an authorized Weatherford representative. Unless noted otherwise, trademarks and service marks herein are the property of Weatherford and may be registered in the United States and/or other countries. Weatherford products named herein may be protected by one or more U.S. and/or foreign patents. For more information, contact patents@weatherford.com. Specifications are subject to change without noice. Weatherford statis its products and services in accordance with the terms and conditions set forth in the applicable contract between Weatherford and the client.

Weatherford Don McRobb Business Unit Leader—Asia Pacific don.mcrobb@ap.weatherford.com Weatherford Jing Heng Hua Senior Technical Sales Engineer jingheng.hua@ap.weatherford.com

© 2013 Weatherford. All rights reserved. 10494.00