

Weatherford®

REAL RESULTS

Premium Hydraulic Liner Set Ahead of Hurricane With No NPT, **All Personnel Evacuate Safely**



Weatherford's premium hydraulic-set static liner hanger is designed for deepwater applications in basins globally and features tight clearances between the liner and host casing. The efficient installation of the liner hanger without any issues enabled the operator to prepare the well for the oncoming hurricane and evacuate all personnel safely.

Objectives

 Perform a liner job quickly and safely before evacuating the wellsite in advance of a hurricane in the Gulf of Mexico. With the hurricane looming, there would be no margin for error.

Results

- Weatherford deployed the premium hydraulic static (PHS) liner hanger system.
- The system successfully ran a 7,000-ft (1233-m) liner to a total depth (TD) of 26,000 ft (7924 m) without any nonproductive time (NPT).
- · Weatherford successfully set the liner, released the running tools, and cemented the liner.
- All personnel were safely evacuated ahead of the storm.

Location

Gulf of Mexico

Well Type

Offshore, oil

Total Depth

26,000 ft (7924 m)

Liner Length

7,000 ft (1233 m)

13 5/8-in., 88.2-lb (40.0-kg) liner set inside 16-in., 110-lb (49.9-kg) casing

Products/Services

- · PHS hydraulic liner hanger
- TSP4 liner-top packer
- Sub-Surface Release[™] mid-bore plugs
- · MBS mechanical ball seat system

Value to Client

- The quick and efficient setting of Weatherford's PHS liner hanger system enabled the operator to prepare the well for the hurricane and provided an optimal starting point to commence further drilling activities after the storm had passed.
- The efficiency of Weatherford's system also enabled all personnel to evacuate the wellsite in a safe and timely manner.

US Region Engineer blake.manuel@weatherford.com

Weatherford products and services are subject to the Company's standard terms and conditions, available on request or at weatherford.com. For more information contact an authorized Weatherford representative. Unless noted otherwise, trademarks and service marks herein are the property of Weatherford and may be registered in the United States and/or other countries. Weatherford products named herein may be protected by one or more U.S. and/or foreign patents. For more information, contact patents@weatherford.com. Specifications are subject to change without notice. Weatherford selfs its products and services in accordance with the terms and conditions set forth in the applicable contract between Weatherford and the client.