

# **Weatherford**<sup>®</sup>

# **REAL RESULTS**

# Arrowhead® Insertable Progressing Cavity Pump Eliminates Need for Workover Rig, Saves Service Time and Cost

# **Objectives**

 Enhance production of a heavy-oil well and save injected gas without using a workover rig. Wells in this field are typically produced with gas lift from a single injection point, but the heaviness of the oil (8° to 14° API) in this well resulted in recirculation of the injected gas without oil production. The operator needed an alternative means of lift to effectively and efficiently produce the well.

# **Results**

- Weatherford's Arrowhead insertable progressing cavity pump (I-PCP) was run in 3 1/2-in. tubing and successfully installed.
- A workover rig was not needed, and this form of artificial lift did not require gas injection.
- After installation of the Arrowhead I-PCP, the well began producing 1.88 B/D (0.3 m³/day) per RPM (revolutions/minute) with a flow rate of 48 to 112 BFPD (5.7 to 13.4 m³/day).

## Value to Client

- Weatherford's I-PCP alternative—the best suited for this heavy-oil application—delivered considerable cost and time savings on this well, leading the operator to use the same solution for other wells.
- Well service costs decreased and workover rig activities were improved as the well operated continuously for more than 390 days.



Weatherford's patented *Arrowhead* I-PCP design reduces the length of the assembly during running and pulling. The pump eliminates the need for production tubing to be pulled and re-run during servicing operations because the rod string is used to install or remove the I-PCP from the well, reducing operational time and cost.

#### Location

Villahermosa, Tabasco, Mexico

#### Flow Rate

48 to 112 BFPD (5.7 to 13.4 m<sup>3</sup>/day)

#### **Casing Size**

7 in. (178 mm), 23 lb/ft

#### **Tubing Size**

3-1/2 in. (89 mm), 9.3 lb/ft

### **Operating Torque**

124 lb/ft

#### **Pump Depth**

2,956 ft (901 m)

#### **Days of Operation**

390 days

#### **Sucker-Rod String**

1 in. x 25 ft Gr D

#### **Products/Services**

- Artificial-lift services
- Arrowhead I-PCP

Weatherford Humberto Machado International Sales Rep humberto.machado@la.weatherford.com Weatherford products and services are subject to the Company's standard terms and conditions, available on request or at weatherford.com. For more information contact an authorized Weatherford representative. Unless noted otherwise, trademarks and service marks herein are the projectly of Weatherford and may be registered in the United States and/or other countries. Weatherford products named herein may be protected by one or more U.S. and/or foreign patents. For more information, contact patents@weatherford.com. Specifications are subject to change without notice. Weatherford selfs its products and services in accordance with the terms and conditions set forth in the applicable contract between Weatherford and the client.