



Weatherford®

REAL RESULTS


Weatherford, Sumitomo Collaborate, Design New Threaded Tubular Makeup/Breakout System, Set Record Torque Value of 375,000 ft-lb

Objectives

- Provide a makeup/breakout system that enabled Sumitomo Metal Industries to perform laboratory and simulated rig-site testing of all of its existing and new premium, integrated connection designs.
- Integrate the system within Sumitomo's SMI testing facility, including being able to conduct tests with real-world conditions on the facility test rig while meeting operational objectives and strict governmental specifications.
- Use a 100% hands-free system to improve personnel safety.

Results

- Working with Sumitomo's operations team, Weatherford custom-designed and built a hands-free, pipe-feeding, hydraulic makeup/breakout system that could accommodate tubulars from 2-3/8 to 20 in. with a maximum weight of 7.5 tons (6.8 metric tons) and provide up to 375,000 ft-lb (508,431 N·m) of torque.
- The horizontal loading frame, specifically designed for Sumitomo, was capable of handling tubulars from 2-3/8 to 20 in. with a maximum weight of 7.6 tons (6.8 metric tons).
- The TorkWizard™ 20-375 Ultra horizontal makeup/breakout unit was newly designed to handle tubulars from 4-1/2 to 20 in. with 375,000 ft-lb (508,431 N·m) maximum torque available for a 20-in. OD tubular.
- Weatherford designed the complete system so that the tubulars could be placed onto the loading frame and each component perform its function before handover to the next stage.



The custom-built, hands-free pipe-feeding, hydraulic makeup/breakout system could accommodate tubulars from 2-3/8 to 20 in. with a maximum weight of 7.5 tons (6.8 metric tons) and provide up to 375,000 ft-lb (508,431 N·m) of torque.



The *PowerFrame* III hydraulic positioning device, the mechanized casing tong CT 14-100, and the TPC-DF torque process control system simulated real rig-site conditions within Sumitomo's testing facility.

Client
Sumitomo Metal Industries

Location
Japan

Products/Services

- Horizontal loading frame
- ComCAM 20-160 bucking unit
- TorkWizard 20-375 Ultra horizontal makeup/breakout unit
- Torque process control (TPC-DF) computer system
- PowerFrame™ III hydraulic positioning device
- CT 14-100 mechanized casing tong

Weatherford
Aaron Sinnott
Tubular Running Services/DwC™
aaron.sinnott@ap.weatherford.com

Daiichi Jitsugyo Co., Ltd.
Yasunori (WILLIE) Yanagisawa
Oil & Gas Exploration Group
yasunori.yanagisawa@dj.k.co.jp

Weatherford products and services are subject to the Company's standard terms and conditions, available on request or at weatherford.com. For more information contact an authorized Weatherford representative. Unless noted otherwise, trademarks and service marks herein are the property of Weatherford and may be registered in the United States and/or other countries. Weatherford products named herein may be protected by one or more U.S. and/or foreign patents. For more information, contact patents@weatherford.com. Specifications are subject to change without notice. Weatherford sells its products and services in accordance with the terms and conditions set forth in the applicable contract between Weatherford and the client.



Weatherford®


REAL RESULTS

Results (continued)

- To simulate real rig conditions during connection testing, a *PowerFrame III*, a mechanized 14-100 casing tong, and a TPC-DF torque monitoring system were provided to test and record the connection designs in vertical positions.
- Operated from the control panel, the entire integrated, mechanized horizontal and vertical makeup/breakout system complied with Sumitomo's objectives and strict government specifications.
- The hands-free solution removed personnel from hazardous areas, improving overall safety.

Value to Client

- Weatherford personnel worked with Sumitomo to integrate particular components within the testing facility and customize those components to meet Sumitomo's requirements and government specifications.
- Weatherford extended Sumitomo's research, development, and testing capabilities for all existing and new tubular connection designs.
- The hands-free operation enabled Sumitomo to safely and efficiently handle tubulars and perform connection testing.



The designed-for-purpose loading frame handles tubulars from 2-3/8 to 20 in. with a maximum tubular weight of 7.5 tons (6.8 metric tons).



The ComCAM 20-160 bucking unit accommodated tubulars from 2-3/8 to 20 in., matching the loading frame's weight and size requirements



The *TorkWizard* 20-375 Ultra unit was designed to meet Sumitomo's specifications and can handle tubulars from 4-1/2 to 20 in. with a maximum torque of 375,000 ft-lb (508,431 N m).

Weatherford products and services are subject to the Company's standard terms and conditions, available on request or at weatherford.com. For more information contact an authorized Weatherford representative. Unless noted otherwise, trademarks and service marks herein are the property of Weatherford and may be registered in the United States and/or other countries. Weatherford products named herein may be protected by one or more U.S. and/or foreign patents. For more information, contact patents@weatherford.com. Specifications are subject to change without notice. Weatherford sells its products and services in accordance with the terms and conditions set forth in the applicable contract between Weatherford and the client.