# Hydrow III Hydraulic-Set Retrievable Production Packer

Isolates the annulus from the production conduit in completions for which a mechanical-set packer is not suitable

## Applications

- · Deviated and horizontal wells
- · Offshore oil and gas completions
- Stacked-packer completions

#### **Features and Benefits**

- The straight-pull, shear-release pins are unaffected by differential pressure, thus enabling easy changes to the release force before running.
- The packer has a cone design instead of hydraulic holddown buttons, which prevents a pressure-induced packer release.
- The compact design of the packer eases its passage through doglegs and deviated wells, which helps to prevent sticking and improve running efficiency.
- The packer can be pressure-tested on-site, which saves rig time and associated costs.
- The setting cylinder is below the elements, which eliminates all of the critical O-rings after setting.
- The packer contains a large flow area that enhances high-volume production or injection.

### **Tool Description**

The Weatherford Hydrow III hydraulic-set, double-grip retrievable production packer has a patented, sequential, upper-slip releasing system. This system releases each slip individually, which results in reduced pull to release the packer. This packer is recommended for use in well completions where the packer is set after the well has been flanged up. Other applications include deviated holes, gas-lift installations, and other completions for which a mechanical-set packer is not suitable.



Hydrow III hydraulic-set retrievable production packer



weatherford.com

© 2009 - 2016 Weatherford. All rights reserved. 11167.02

Weatherford products and services are subject to the Company's standard terms and conditions, available on request or at weatherford.com. For more information contact an authorized Weatherford representative. Unless noted otherwise, trademarks and service marks herein are the property of Weatherford and may be registered in the United States and/or other countries. Weatherford products named herein may be protected by one or more U.S. and/or foreign patents. Specifications are subject to change without notice. Weatherford sells its products and services in accordance with the terms and conditions set forth in the applicable contract between Weatherford and the client.

# Hydrow III Hydraulic-Set Retrievable Production Packer

#### **Specifications**

Casing				Packer			
OD	Weight	ID		Maximum	Minimum	Standard Thread	Product
		Minimum	Maximum	OD	Minimum ID	Connection	Number
9.625 in.	40.0 to 47.0 lb/ft	8.681 in.	8.835 in.	8.500 in.	4.845 in.	5 ½-in., LTC 8 RD	733694
244.50 mm	59.5 to 69.9 kg/m	220.50 mm	224.41 mm	215.90 mm	123.06 mm	5 ½-in., 17 lb, VAM TOP®	1311686



\* VAM TOP is a registered trademark of Vallourec Mannesmann Oil & Gas France Corporation.

weatherford.com

© 2009 - 2016 Weatherford. All rights reserved. 11167.02

Weatherford products and services are subject to the Company's standard terms and conditions, available on request or at weatherford com. For more information contact an authorized Weatherford representative. Unless noted otherwise, trademarks and service marks herein are the property of Weatherford and may be registered in the United States and/or other countries. Weatherford products named herein may be protected by one or more U.S. and/or foreign patents. Specifications are subject to change without notice. Weatherford sells its products and services in accordance with the terms and conditions set forth in the applicable contract between Weatherford and the client.