



ISO-Flow Screen

Weatherford's ISO-Flow screen offers an innovative way of isolating perforations without any major changes in standard job procedures or the addition of rig time. The ISO-Flow screen is constructed using Weatherford's WXD sliding sleeve and nonperforated base pipe. The sliding sleeve and base pipe subassembly are placed inside a jacket of Super-Weld® screen to create the ISO-Flow screen, providing both effective sand control and selective production, injection, or isolation of the perforated interval.

For wells that are fluid sensitive or have extremely low bottomhole pressure, the ISO-Flow screen can prevent fluid loss after the gravel pack by closing the sleeve. After a circulating gravel pack is performed, the shifting tool installed on the washpipe closes the sleeve as the crossover tool is pulled from the well. During production operations, the WXD sleeve is opened or closed on slickline with a standard B-type shifting tool.

For wells with multiple zones, individual zones can be produced or shut-in as reservoir or market conditions warrant. In gravel packing, a long, horizontal well with water or gas cap drive, an ISO-Flow screen can be placed with isolation packers to control unwanted water cut or gas cut by closing the WXD sliding sleeve, removing the contribution from that interval.

The ISO-Flow screen is built to order with specified pipe grades, threads, and wire metallurgy.

Applications

- Squeeze-gravel packs
- Circulating gravel packs
- Fluid-loss control
- Selective production, injection, or isolation

Features, Advantages and Benefits

- Field-proven *Super-Weld* screen coupled with WXD sliding sleeve provides economical and effective zonal shutoff in gravel-packed wells, lowering maintenance costs.
- ISO-Flow screen can provide immediate zone isolation after gravel packs and stimulation treatments, enhancing well operation safety and preventing fluid loss or well flow.
- The capability to select production from gas and oil zones within a common well enables operators to change production profiles based on changing needs, contractual requirements, or peak season rates, providing operational flexibility.





ISO-Flow Screen

Specifications

Base Pipe			Screen			
Size (in.)	Weight (lb/ft)	Base Pipe ID (in./mm)	Seal Bore ID - WXD (in./mm)	Screen Housing OD (in./mm)	End-Ring OD (in./mm)	Part Number
2-7/8	6.4	2.441 62.0	1.875 47.6	3.460 87.9	3.660 93.0	1392625
3-1/2	9.2	2.992 76.0	2.313 58.7	4.077 103.6	4.280 108.7	1392626
4-1/2	11.6	4.000 101.6	2.813 71.4	5.161 131.1	5.365 136.3	1392627

For Internal Use:

Link to Endeca assembly numbers: [ISO-Flow Screen](#)