Wellhead Outlet

Connects the permanent downhole cable to an armored surface cable

Applications

NEED THIS

Features and Benefits

- NEED
- THIS

Tool Description

The Weatherford wellhead outlet connects the permanent downhole cable (TEC Line) to an armored surface cable while isolating the electrical connection in an explosion- proof housing. The outlet provides a dual safety barrier to prevent well fluid migration to the surface. High-quality Swagelok fittings are an integral part of the design.

Specifications

Ratings and dimensions

Ratings and annichatons	
Maximum pressure	15,000 psi
TEC line fittings OD	Standard ¼-in. OD (Other sizes to order)
Length	15.78 in. (400.8 mm)
Weight	10.0 lb (1.36 kg)
Mounting	½-in. Male NPT (Other sizes to order)
Materials	316 SS
Pressure test	Field pressure testable to 5k psi

Flectrical specification

Ziooti iodi opoomiodiion	
Voltage	24 vDC
Standards met	NEC/CEC:Class I, Division 1 & 2, Groups B, C, D;Class II, Division 1, Groups E, F, G;Class II, Division 2, Groups F, G Class III;UL Standard: 1203;ANSI Standard: C33.27;CSA Standard: C22.2 No. 30;NEMA/ EEMAC 3, 4





weatherford.com © 2024 Weatherford. All rights reserved. 14027.00

WIRELINE TECH SPECS





weatherford.com© 2024 Weatherford. All rights reserved.14027.00