

## COROD<sup>®</sup> Deployment Trailer

Provides an excellent COROD transport alternative for regions with restrictive weight and dimension limits

### Applications

- Transporting COROD continuous rod strings
- Operating in conjunction with primary equipment to install and retrieve COROD continuous rod strings

### Features and Benefits

- The highly compact design of the deployment trailer significantly reduces the overall dimensions of the unit, which facilitates operation in regions with restrictive weight limits.
- The ergonomic and practical design minimizes pinch points, which reduces the risk of injury.
- The unit can be transported using the Weatherford Mobile Gripper<sup>™</sup> unit or using a client's pre-existing equipment for convenience.



### Tool Description

The Weatherford COROD deployment trailer is a smaller, more compact transport unit than our standard COROD transport trailer. The COROD deployment trailer is compatible with the Weatherford small reel design, which has the capacity to hold up to 6,078 ft (1,852 m) of 1-in. (25.4-mm) COROD continuous rod string. The trailer supports all sizes of COROD continuous rod and is a reliable solution for shipping continuous rod strings from a Weatherford warehouse base to the client's wellsite. The COROD deployment

trailer is equipped with a hydraulic power system that operates the hydraulic rotating hub, transfer unit, and rod straightener for running COROD continuous rod from the small transport reel into the well without human intervention. All Weatherford transport trailers are constructed with safety as the top priority. Rod-handling safety devices, such as locking tools for load securement and the brake system for control of the hub speed, are incorporated into the trailer design to reduce pinch points and the potential for injury.



# COROD<sup>®</sup> Deployment Trailer

## Specifications

### Trailer

Length	26.2 ft (7.98 m)
Width, loaded	8.8 ft (2.72 m)
Height, loaded	13.1 ft (4.00 m)
Weight, loaded	31,244 lb (14,172 kg)
Weight, unloaded	13,955 lb (6,330 kg)
Supported types of COROD continuous rod	Round

### COROD Continuous Rod

COROD No.	Size	Weight	Maximum Length	Maximum Weight
8.5R	1-5/32 in. (29.4 mm)	3.57 lb/ft (5.32 kg/m)	4,548 ft (1,387 m)	16,236 lb (7,379 kg)
6R	1 in. (25.4 mm)	2.67 lb/ft (3.98 kg/m)	6,078 ft (1,852 m)	16,228 lb (7,371 kg)
4R	7/8 in. (22.2 mm)	2.04 lb/ft (3.05 kg/m)	7,905 ft (2,410 m)	16,126 lb (7,351 kg)
3R	13/16 in. (20.6 mm)	1.76 lb/ft (2.63 kg/m)	9,265 ft (2,824 m)	16,306 lb (7,427 kg)

\* CORODO is a registered trademark of Weatherford in the US, Argentina, Australia, Canada, Colombia, Kazakhstan, Mexico, Oman, Romania, the Russian Federation, and Venezuela.

