

# COROD<sup>®</sup> Single Reel Transport Trailer

Offers a safe and reliable solution for shipping continuous rod strings to the client's wellsite

## Applications

- Transporting COROD continuous rod strings
- Operating in conjunction with primary equipment to install and retrieve COROD continuous rod strings

## Features and Benefits

- The rotating hub allows COROD continuous rod to be removed from and installed onto the transport reel while on the transport trailer, providing greater convenience.
- For added safety, the rod support and containment arms provide control and secondary containment of COROD continuous rod strings during operation.
- The ergonomic and practical design minimizes pinch points, which reduces the risk of injury.

## Tool Description

The Weatherford COROD single reel transport trailer is a compact, fit-for-purpose tandem-axle transport trailer capable of moving the equivalent of 7,200 ft (2195 m) of 1-in. (25.4-mm) COROD continuous rod string per unit. The COROD transport trailer supports all sizes of COROD continuous rod. It is a reliable solution for shipping continuous rod strings from the Weatherford warehouse base to the client's wellsite.

When operating with primary equipment, COROD continuous rod can be run from the single reel trailer directly into the well. An



The COROD single reel transport trailer is equipped with a rotating hub for aligning and restraining the transport reel and locking devices for securing the load during transit.

integral hydraulic system is also included for raising and lowering the transport reel.

All COROD single reel transport trailers are constructed with safety as the top priority. Rod-handling safety devices, such as the brake system used to control the hub speed, are incorporated in the unit's design, and pinch points are minimized to reduce the potential for injury.



# COROD<sup>®</sup> Single Reel Transport Trailer

## Specifications

Weight, loaded	29,920 lb (13,571 kg)
Weight, unloaded	8,003 lb (3,630 kg)
Supported COROD continuous rod types	Round, semi-elliptical
Rig-in/rig-out time	30 min

COROD Continuous Rod				
COROD No.	Size	Weight	Maximum length	Maximum weight
8.5R	1-5/32 in. (29.4 mm)	3.57 lb/ft (5.32 kg/m)	5,350 ft (1,631 m)	19,100 lb (8,664 kg)
6R	1 in. (25.4 mm)	2.67 lb/ft (3.98 kg/m)	7,200 ft (2,195 m)	19,224 lb (8,719 kg)
4R	7/8 in. (22.2 mm)	2.04 lb/ft (3.05 kg/m)	9,300 ft (2,834 m)	18,972 lb (8,605 kg)
3R	13/16 in. (20.6 mm)	1.76 lb/ft (2.63 kg/m)	10,850 ft (3,307 m)	19,096 lb (8,662 kg)
8	18/16 in. (28.6 mm)	3.38 lb/ft (5.03 kg/m)	5,625 ft (1,715 m)	19,013 lb (8,624 kg)
7	17/16 in. (27.0 mm)	3.01 lb/ft (4.49 kg/m)	6,325 ft (1,928 m)	19,038 lb (8,635 kg)
6	16/16 in. (25.4 mm)	2.67 lb/ft (3.98 kg/m)	7,200 ft (2,195 m)	19,224 lb (8,720 kg)
5	15/16 in. (23.8 mm)	2.35 lb/ft (3.50 kg/m)	8,100 ft (2,469 m)	19,035 lb (8,634 kg)
4	14/16 in. (22.2 mm)	2.04 lb/ft (3.05 kg/m)	9,300 ft (2,834 m)	18,972 lb (8,605 kg)
3	13/16 in. (20.6 mm)	1.76 lb/ft (2.63 kg/m)	10,850 ft (3,307 m)	19,096 lb (8,662 kg)
2	12/16 in. (19.1 mm)	1.5 lb/ft (2.24 kg/m)	12,700 ft (3,870 m)	19,050 lb (8,641 kg)

COROD is a registered trademark of Weatherford in the US, Venezuela, Canada, Argentina, the Russian Federation, Colombia, Mexico, Kazakhstan, Romania, Oman, Mexico, and Australia.

