

Magnus[®] Rotary Steerable System

Combines reliable, high-performance drilling with precise directional control

Applications

- Single-run vertical, curve, and lateral drilling
- High dogleg-severity (DLS) applications
- Extended-reach drilling
- High-performance, motorized rotary-steerable drilling when combined with the Weatherford HyperLine[™] drilling motor
- Geosteering applications when combined with the Weatherford Wave[™] suite of logging-while-drilling (LWD) sensors

Features and Benefits

- Tri-actuator design with independent pad control increases reliability through redundancy, achieves a true-inclination hold, and creates a smooth wellbore.
- Fully rotating design and optimized junk slot area reduce risk of stuck pipe events.
- Rugged yet simple construction facilitates servicing, even in remote locations.
- Sensors located just 6 ft behind the bit provide accurate inclination and gamma readings for effective wellbore placement and geosteering changes.
- High-frequency control system provides rapid sample rate to verify location and optimize control in high-rpm applications and adverse vibrational drilling environments.
- On-the-fly downlinking using the DownLink Commander[®] bidirectional communication technology quickly confirms information and makes immediate steering adjustments.
- High-dogleg capability increases pay-zone contact.

Tool Description

Using push-the-bit technology, the Weatherford Magnus rotary steerable system (RSS) delivers high-performance drilling with precise directional control. In nearly any environment or application, the RSS offers rugged design elements to sustain reliability and drilling efficiencies to deliver a quality wellbore ahead of time.

The RSS is compatible with the Weatherford Wave suite of LWD sensors to fulfill formation-evaluation or geosteering requirements. It also combines with RipTide[®] tools for underreaming while drilling.



The Weatherford Magnus RSS has a push-the-bit design with features that improve drilling performance.

Optimized junk slot area

Near-bit inclination and azimuthal gamma sensors

Independent pad control



Magnus[®] Rotary Steerable System

Specifications

Mechanical

RSS	Magnus 475	Magnus 675	Magnus 825	Magnus 950	Magnus 1100	
BIAS collar size	5 in.	7 in.	8-3/8 in.	9-1/2 in.	11 in.	
Hole size range	5-7/8 to 6-3/4 in.	8-3/8 to 9-1/4 in.	9-7/8 to 10-5/8 in.	12 to 14-1/2 in.	14-3/4 to 18-1/2 in.	
Minimum overall tool length	17.0 ft (5.2 m)	17.0 ft (5.2 m)	17.45 ft (5.3 m)	18.2 ft (5.5 m)	18.2 ft (5.5 m)	
Overall tool weight ¹	900 lb (408 kg)	1,850 lb (840 kg)	2,850 lb (1,293 kg)	3,750 lb (1,700 kg)	5,275 lb (2,600 kg)	
Top connection	3-1/2 in. IF (NC 38) box	4-1/2 in. IF (NC 50) box	5-1/2 in. IF box	5-1/2 in. IF box	5-1/2 in. IF box (8-1/4 in. barrel collar)	7-5/8 in. API Reg box (9-1/2 in. barrel collar)
Makeup torque (top)	9,900 to 10,900 ft-lb (13,424 to 14,740 N·m)	30,000 to 33,000 ft-lb (40,675 to 44,740 N·m)	53,000 to 56,000 ft-lb (71,860 to 75,925 N·m)	53,000 to 56,000 ft-lb (71,860 to 75,925 N·m)	53,000 to 56,000 ft-lb (71,860 to 75,925 N·m)	75,000 to 78,000 ft-lb (101,690 to 105,755 N·m)
Bottom connection	3-1/2 in. API Reg box	4-1/2 in. API Reg box	6-5/8 in. API Reg box	6-5/8 in. API Reg box	7-5/8 in. API Reg box	
Makeup torque (bottom)	6,300 to 6,900 ft-lb (8,500 to 9,400 N·m)	20,000 to 22,000 ft-lb (27,115 to 29,830 N·m)	28,000 to 32,000 ft-lb (37,960 to 43,385 N·m)	28,000 to 32,000 ft-lb (37,960 to 43,385 N·m)	58,000 to 64,000 ft-lb (78,635 to 86,770 N·m)	
Maximum tension	300,000 lbf (133,447 daN)	610,000 lbf (271,342 daN)	1,000,000 lbf (444,822 daN)	1,125,000 lbf (500,424 daN)	1,550,000 lbf (689,474 daN)	
Maximum operating torque at the bit	8,840 ft-lb	17,850 ft-lb	25,500 ft-lb	25,000 ft-lb	51,850 ft-lb	
Maximum drilling rpm ²	350	300	300	300	300	
Maximum weight on bit	Limit based on bit specifications					
Dogleg severity (DLS) capability ³	12°	10°	6°	6°	5°	
Minimum kickoff angle vertical	No limit, kick off from vertical					
Maximum operating pressure	30,000 psi (206.8 MPa)	30,000 psi (206.8 MPa)	25,000 psi (172.4 MPa)	25,000 psi (172.4 MPa)	25,000 psi (172.4 MPa)	
Maximum operating temperature	302°F (150°C)					
Maximum flow rate	350 gal/min (1,325 L/min)	700 gal/min (2,650 L/min)	1,200 gal/min (4,524 L/min)	1,200 gal/min (4,542 L/min)	1,400 gal/min (5,300 L/min)	

¹ Tool weight is for the standard configuration.

² Maximum rpm is the average, not the peak, rpm.

³ Dogleg severity is in degrees per 100 ft (30 m).



Magnus[®] Rotary Steerable System

Specifications (continued)

Mechanical

RSS	Magnus 475	Magnus 675	Magnus 825	Magnus 950	Magnus 1100
Maximum pass-thru dogleg (rotating) ¹	15°	14°	7°	6°	6°
Maximum pass-thru dogleg (sliding) ¹	30°	17°	14°	12°	12°
Maximum sand content	2%				
Maximum LCM content	50 lb/bbl (non-fibrous)				
Near-bit inclination sensor to bit box	5.5 ft (1.7 m)	6.0 ft (1.8 m)	6.1 ft (1.9 m)	6.85 ft (2.1 m)	6.85 ft (2.1 m)

¹ The RSS may require a high-DL-specific BHA configuration.

Azimuthal Gamma Ray (Optional)

RSS	Magnus 475	Magnus 675	Magnus 825	Magnus 950	Magnus 1100
Gamma ray sensor to bit box	6.0 (1.8 m)	6.4 ft (1.9 m)	6.5 ft (2.0 m)	7.2 ft (2.2 m)	7.2 ft (2.2 m)
Measurement range, AAPI	0 to 500 API	0 to 750 API			
Accuracy at 100 API	±2.5 API				
Vertical resolution ¹	14.5 in. (370 mm)	15.0 in. (380 mm)	16.0 in. (410 mm)	16.5 in. (420 mm)	19 in. (480 mm)

¹ Vertical resolution indicates the distance over which 90% of the response occurs.



Magnus[®] Rotary Steerable System

Specifications (continued)

Drilling Dynamics

RSS	Magnus 475	Magnus 675	Magnus 825	Magnus 950	Magnus 1100
Measurements	Axial vibration, lateral vibration, RPM, low-frequency torsional oscillation (LFTO) stick-slip high-frequency torsional oscillation (HFTO)				
Vibration measurement range ¹	0 to 250 g				
Sample rate	1,024 Hz				
Measurement range for rpm	0 to 833 rpm				
Identifiable frequency range	0 to 350 Hz				

¹ Range is relevant to axial, lateral, and tangential vibration measurements.

